


TKC 45 TKMC 45 SERIES

CLOSED
OPENABLE TOP AND
BOTTOM
With VERTICAL
HORIZONTAL
DIVIDERS +
CLIPS



| | A | C | KR | P | M/M | PS-KG/M |
|------------------|-----|-----|----------------------------------|------|-------|---------|
| MODEL TKC 45/50 | 82 | 50 | 75-100-125 150-200-250 300 | 70,6 | 14,16 | 2,30 |
| MODEL TKC 45/75 | 107 | 75 | | ... | ... | 2,42 |
| MODEL TKC 45/100 | 132 | 100 | | ... | ... | 2,55 |
| MODEL TKC 45/125 | 157 | 125 | | ... | ... | 2,67 |
| MODEL TKC 45/150 | 182 | 150 | | ... | ... | 2,79 |
| MODEL TKC 45/175 | 207 | 175 | | ... | ... | 2,91 |
| MODEL TKC 45/200 | 232 | 200 | | ... | ... | 3,03 |
| MODEL TKC 45/250 | 282 | 250 | | ... | ... | 3,27 |
| MODEL TKC 45/300 | 332 | 300 | | ... | ... | 3,51 |

| | | |
|--|----------|-------|
| STROKE LENGTH | SEE PAGE | 14 |
| CABLE CARRIER LENGTH | SEE PAGE | 14 |
| SELF-BEARING LENGTH IN RELATION TO ADDITIONAL WEIGHT | SEE PAGE | 14-15 |
| NON-STANDARD or SPECIAL FLANGES | SEE PAGE | 11 |
| LOCKING ELEMENTS | SEE PAGE | 12 |
| ASSEMBLY VARIANTS | SEE PAGE | 9-10 |
| FOR OTHER TECHNICAL DATA: MODEL TKK45 | SEE PAGE | 24 |

S = 16

A = (C1 + C2 + C3) + (S x N. of Bands)

A_{MAX} = 2000

N. of bands selectable.

